

Apollo 1500



105
Thredbo



175
Franklin



515
Pyrenees



525
Alpine Gum



535
Derwent



545
Blackbutt



551
Daintree



556
Spotted Gum



571
Sherbrooke



721
Cumberland



730
Boston



790
Midnight

Apollo 1500

Apollo 1500 is a stunning hybrid floor that is extremely hard wearing and stable with a waterproof surface[^], making it perfect for use in all areas of your home. With micro bevel edges and an embossed matte finish, Apollo 1500 authentically replicates a natural timber wood grain look. A scratch and stain resistant surface coating means Apollo 1500 can easily withstand the everyday wear and tear of busy family homes.

Technical Data

Type:	Hybrid Flooring	Finish:	Matte
Dimensions:	1500mm x 180mm	Surface:	Embossed
Thickness:	6.5mm	Top Layer:	Decorative Film & Wear Layer
Wear Layer:	0.5mm	Substrate Layer:	Trigon® Core Technology (Limestone Composite)
Units Per Box:	6 boards	Backing Layer:	1.5mm Acoustic Backing
m² per box:	1.62	Profile:	Micro Bevel
m² per pallet:	113.4	Coating System:	PUR & Scratch Resistance
Colours:	12	Installation Method:	Uniclic®

Performance

Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: -0.00%, Curling: 0.00%	Light Fastness:	(EN ISO 105-B02) Grade 6
Thermal Resistance:	(EN 12667) 0.056m ² .K/W	Light Reflectance Values:	Available on Request
Thermal Conductivity:	(EN 12667) 0.115 W/(m.K)	Flammability:	(EN ISO 9239) CRF 10.9kW/m ²
Abrasion Rating:	(EN 660-2) Group T	Smoke Value:	(EN ISO 9239) 81% minutes
Swelling after submersion in water:	(ISO 24336) 0.3%	Slip Resistance:	(AS 4586) P3
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet	Warranty:	25 Year Hybrid Limited Residential Warranty*

Sustainability

Product Transparency:	Global Green Tag, GreenRate Level A certified
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Global Green Tag:	GreenRate Level A Certified
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.
 *This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the full terms and conditions available from your retailer, by calling 1300 444 776, or by download from www.godfreyhirst.com.
 † Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.
 ^Subject to proper installation, maintenance and local building code/regulatory approval.

Apollo 1500



Mid Range