

Apollo









180 Python



Sunlight



510 Enlighten



Bronze



Wreath



545 New Eng Blackbutt



Grafton Spot.Gum



Western Blackbutt



Tallowood



Oracle



Dolphin

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. godfreyhirst.com



Apollo

Apollo captures the natural beauty of timber with the best attributes of a laminate and vinyl flooring. The innovative hybrid flooring delivers astonishing durability and impact resistance.

Technical Data

Туре:	Hybrid Flooring	Finish:	Matte
Dimensions:	1220mm x 180mm	Surface:	Embossed
Thickness:	5.8mm	Top Layer:	Decorative Film & Wear Layer
Wear Layer:	0.3mm	Substrate	Trigon® Core Technology (Limestone Composite)
Units Per Box:	10	Layer:	
		Backing Layer:	1.5mm Acoustic Backing
m ² per box:	2.196	Buoking Luyon	1.onin / locablic Babking
m ² per pallet:	131.76	Profile:	Micro Bevel
Colours:	12	Coating	UV Coating
colours.	12	System:	
		Installation	Drop Lock
		instanation	DIOP LOOK

Method:

Performance

Dimensional	(ISO 23999) Length: 0.05%, Width:	Light Fastness:	(EN ISO 105-B02) Grade 6
Stability:	-0.05%, Curling: 0.00%	Light	Available on Request
Thermal Resistance:	(EN 12667) 0.061m ² .K/W	Reflectance Values:	
Thermal	(EN 12667) 0.101 W/(m.K)	Flammability:	(EN ISO 9239) CRF 10.6kW/m2
Conductivity:		Smoke Value:	(EN ISO 9239) 92% minutes
Abrasion Rating:	(EN 660-2) Group T	Slip Resistance:	(AS 4586) P3
Swelling after submersion in	(ISO 24336) 0.1%	Warranty:	15 Year Hybrid Limited Residential Warranty*
water:			
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet		

Sustainability

Product Transparency:	Global Green Tag, GreenRate Level A certified
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Global Green Tag:	GreenRate Level A Certified
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits















Global Green Tag

ISO 9001 ISO 14001

SO **9001**

Micro Bevel Edge

Embossed

Matte Finish

Waterproof Surface^

15 Year Hybrid 0.3mm Wear layer Limited Residential Warranty*



All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions. "This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com. I Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager. ^Subject to proper installation, maintenance and local building code/regulatory approval.





Affordable



