

Metropol 1500





Alabaster



Burnt Umber



300 Sable Oak



500 Cornsilk



Brass Oak



Apple-Box Gum



Marble Spotted Gum



560 Burl Oak



Fallow Oak



Platinum Grey



Pepper Oak



790 Silhouette Oak

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. godfreyhirst.com

Godfrey Hirst

Metropol 1500

Delivering super durable and impact resistant flooring with exquisite design, Metropol 1500 is a technologically advanced hybrid range that ticks all the right boxes. Available in a wide range of natural timber hues, your next project is a guaranteed winner with strong, stable and beautiful flooring that's easy to install.

Technical Data

Туре:	Hybrid Flooring	Finish:	Matte
Dimensions:	1500mm x 228mm	Surface:	Embossed
Thickness:	6.5mm	Top Layer:	Decorative Film & Wear Layer
Wear Layer:	0.5mm	Substrate	Trigon® Core Technology (Limestone Composite)
Units Per Box:	6 boards	Layer:	
	0 000100	Backing Layer:	1.5mm Acoustic Backing
m ² per box:	2.052	Buoking Luyon	1.onin / locuolic Baoking
m ² per pallet:	123.12	Profile:	Micro Bevel
		Coating	PUR
Colours:	12	System:	
		Installation	Uniclic®

Method:

Performance

Dimensional	(ISO 23999) Length: 0.0, Width: 0.0,	Light Fastness:	(EN ISO 105-B02) ≥6
Stability:	Curling: 0.0	Light Reflectance Values:	Available on Request
Thermal Resistance:	(ISO 8301) 0.039m².K/W		
Thermal	(ISO 8301) 0.128 W/(m.K)	Flammability:	(EN ISO 9239) CRF 11.1kW/m2
Conductivity:		Smoke Value:	(EN ISO 9239) 210% minutes
Abrasion	(EN 660-2) Group T		. ,
Rating:		Slip Resistance:	(AS 4586) P3
Swelling after submersion in	(ISO 24336) 0.1%	Warranty:	25 Year Hybrid Limited Residential Warranty*
water:			
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet		

Sustainability

Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Indoor Air Quality:

Green Building Council Compliant for VOC emission rate limits



















ISO 14001 Micro Bevel Edge

Matte Finish

Waterproof Surface^

Limited Residential

0.5mm Wear Layer



ISO 9001

Embossed

25 Year Hybrid Warranty

Mid Range

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions. "This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, bease refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com. 1 Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager. ^Subject to proper installation, maintenance and local building code/regulatory approval.